


PRODUCT DESCRIPTION

- Fixed output build in LED Driver.
- Constant Current LED Driver.
- Nominal Life-Time Upto 30,000 hr.
- 3/5-Years Warranty.
- High Voltage withstanding capacity 440V AC.
- CE (Certified).
- IS 15885 (Part 2/Sec 13).
- IS 16104.
- IEC 60950-1.
- IEC 61000-4-5.



Input Characteristics

| | | |
|----|-----------------------------|----------------------|
| 1 | Voltage (Un) | 240 Vac |
| 2 | Operating Voltage Range | 100 ~300 Vac |
| 3 | Frequency (Hz) | 50 / 60 Hz |
| 4 | Maximum Input Current | 0.67A |
| 5 | Input Power (W) | 160W |
| 6 | Power Factor (PF) | > 0.98 |
| 7 | Inrush current Protection | Yes |
| 8 | Current Harmonics (Athd) | < 10% |
| 9 | Surge Withstanding Capacity | 6 KV |
| 10 | Over Voltage Cutoff | 320V (Tole : +/-10V) |
| 11 | Under Voltage Cutoff | 110V |
| 12 | Automatic Restart | 300V |
| 13 | Driver Life | >30000Hrs |

Mechanical Details

| | | |
|---|---|-----------|
| 1 | Weight | 440gm |
| 2 | Case Dimensions | |
| | Length W/Mount | 187mm |
| | Center to Center (CTC) | 174mm |
| | Width | 68mm |
| | Height | 41mm |
| 3 | Case Material | Metal Box |
| 4 | Wiring Diagram | On Screen |
| 5 | Input / Output Terminals | NA |
| 6 | Wires Length | |
| 7 | Input (3 Core or single core- White(L,N) & Green- | 300mm |
| 8 | Output (Single Core Wire- Red(+),Black(-) | 300mm |
| 9 | Potting | IP65 |

Output Characteristics

| | | |
|---|---|----------------------|
| 1 | Output short circuit protection and Restart | Yes |
| 2 | Thermal Protection | Yes |
| 3 | No-Load Protection | Yes |
| 4 | Max Output Current | 800MA (Tole : +/-3%) |
| 5 | Output Voltage | 160-180V |
| 6 | Output Power (W) | 144W max |
| 7 | Efficiency | >88% |

Key Features

| | |
|---|--|
| 1 | Compact Design |
| 2 | High Voltage withstanding capacity |
| 3 | High Surge withstanding capacity |
| 4 | Long Life |
| 5 | High Durability |
| 6 | Automatic Restart after Safe Voltage Mode. |


Environmental Operating Details

| | | |
|---|------------------------------|-------------------|
| 1 | Minimum Starting Temperature | -30°C ... 75°C |
| 2 | Max. Ambient Temperature | -20°C ... to 65°C |
| 3 | Max. Case temperature (Tc) | 85°C |

Metal Box



Bottom



Top

